










The FSLW is similar to the FSL, but is designed for use in rice paddies.
Standard (type of) lug shape and arrangement with superior traction performance in normal to moist soil conditions.
Excellent self-cleaning performance.

FARM SERVICE LUG-W
FSLW (R-1)

DIMENSION

 SIZE	PLY	TYPE			TW		NO. OF LUG			MAX SPEED 30km/h				VALVE
			(mm)	(mm)		(mm)		(mm)	(mm)	INFL.		MAX.L		
										(kPa)	(psi)	(kg)		
6-12	2	TT	572	155	145	16	16	1691	264	120	17	205	5JA	TR13
6.00-16	4	TT	741	161	170	25	15	2216	346	180	26	400	4.00E	TR15
6.00-16	6	TT	741	161	170	25	15	2236	349	250	37	505	4.00E	TR15
6.00-16	8	TT	741	161	170	25	15	2229	348	340	50	585	4.00E	TR15
7-16	4	TT	738	169	176	28	15	2197	343	180	26	405	5JA	TR15
8-16	4	TT	783	187(192)	220	31	14	2306	360	160	23	475	5JA(5.50F)	TR15,218A
7.2-20	4	TT	841	179	180	28	17	2511	392	180	26	480	W6	TR15
7.2-24	4	TT	944	179	180	28	19	2818	440	180	26	555	W6	TR15,218A
9.5-24	4	TT	1047	232	236	33	17	3075	480	140	20	740	W7	TR15,218A
9.5-24	6	TT	1047	232	236	33	17	3126	488	220	31	940	W7	TR15,218A
11.2-24	4	TT	1088	270	260	35	15	3177	496	120	17	845	W9	TR15,218A
11.2-24	6	TT	1088	270	260	35	15	3241	506	180	26	1045	W9	TR15,218A