

■ **IMPORTANT**

- Do not turn front discs to obtain wider tread.

■ **NOTE**

- Wheels with beveled or tapered holes: use the tapered side of lug nut.

9Y1210369GEG0080US0

(2) Front Wheels (4WD Type)

Front axle is not adjustable

<p>9Y1210369GES032A</p>	Models	L3240, L3540					
	Tire	7-16, 7.2-16 Farm	—	27 × 8.50- 15 Turf	27 × 10.50- 15 Turf	29 × 12.50- 15 Turf	10-16.5 IND
	Tread	1115 mm (45.5 in.)	—	1200 mm (47.2 in.)	1230 mm (48.4 in.)	1170 mm (46.1 in.)	1235 mm (48.6 in.)
	Models	L3940					
	Tire	—	8-16, 8.3-16 Farm	27 × 8.50- 15 Turf	27 × 10.50- 15 Turf	29 × 12.50- 15 Turf	10-16.5 IND
	Tread	—	1155 mm (45.5 in.)	1200 mm (47.2 in.)	1230 mm (48.4 in.)	1170 mm (46.1 in.)	1235 mm (48.6 in.)
	Models	L4240, L4740					
	Tire	—	8-16, 8.3-16 Farm	27 × 10.50- 15 Turf	29 × 12.50- 15 Turf	305R343 Turf	10-16.5 IND
	Tread	—	1300 mm (51.2 in.)	1375 mm (54.1 in.)	1425 mm (56.1 in.)	1455 mm (57.3 in.)	1380 mm (54.3 in.)
	Models	L5040, L5240, L5740					
	Tire	—	9.5-16 Farm	27 × 10.50- 15 Turf	29 × 12.50- 15 Turf	305R343 Turf	10-16.5 IND
	Tread	—	1340 mm (52.8 in.)	1375 mm (54.1 in.)	1425 mm (56.1 in.)	1455 mm (57.3 in.)	1380 mm (54.3 in.)

■ **NOTE**

- IND: for industrial

9Y1210369GEG0081US0

(3) Rear Wheels





Rear tread can be adjusted in 6 steps depending on the model.


To change the tread

1. Lift the rear tires off the ground.
2. Follow the illustrations below to get the desired tread width.

■ **IMPORTANT**

- If not attached as illustrated, transmission parts may be damaged.
- When re-fitting or adjusting a wheel, tighten the bolts to the following torques then recheck after driving the tractor 200 m (200 yards) and thereafter according to service interval.

Models	 9Y1210369GES033A	 9Y1210369GES034A	 9Y1210369GES035A	 9Y1210369GES036A
L3240, L3540 12.4-24 Farm	1200 mm (47.2 in.)	1300 mm (51.2 in.)	1385 mm (54.5 in.)	1480 mm (58.3 in.)
L3940, L4240, L4740 14.9-24 Farm	—	1285 mm (50.6 in.)	1435 mm (56.5 in.)	1530 mm (60.2 in.)
L3240, L3540 420/70-24 IND	—	1325 mm (52.2 in.)	1360 mm (53.5 in.)	1465 mm (57.7 in.)
L3940, L4240, L4740 17.5L-24 IND	—	1340 mm (52.8 in.)	1380 mm (54.3 in.)	1490 mm (58.7 in.)
L5040, L5240, L5740 13.6-28 Farm	1220 mm (48.0 in.)	1330 mm (52.4 in.)	1425 mm (56.1 in.)	1530 mm (60.2 in.)
L5040, L5240, L5740 14.9-26 Farm	—	—	1325 mm (52.2 in.)	1430 mm (56.3 in.)
L5040, L5240, L5740 17.5L-24 IND	—	1360 mm (53.5 in.)	1395 mm (54.9 in.)	1500 mm (59.1 in.)

Models	 9Y1210369GES037A
L4240, L4740, L5040, L5240, L5740 610R470 Turf	1515 mm (59.6 in.)
L3240, L3540 355/80-D20 Turf	1270 mm (50.0 in.)
L3940 355/80-D20 Turf	1290 mm (50.8 in.)
L3240, L3540 41/18LL × 16.1 Turf	1420 mm (55.9 in.)
L3940, L4240, L4740, L5040, L5240, L5740 41/18LL × 16.1 Turf	1440 mm (56.7 in.)
L3240, L3540 44 × 18-20 Turf	1400 mm (55.1 in.)
L3940, L4240, L4740, L5040, L5240, L5740 44 × 18-20 Turf	1415 mm (55.7 in.)

9Y1210369GEG0082US0