

BUCKET SPECIFICATIONS

LOADER MODEL		LA765		
MODEL		SQUARE 72"	ROUND 72" HD	SQUARE 72" LIGHT MATERIAL
TYPE		QUICK ATTACH	QUICK ATTACH	QUICK ATTACH
WIDTH	mm (in.)	1830 (72)		
DEPTH (L)	mm (in.)	547 (21.5)	477 (18.8)	607 (23.9)
HEIGHT (M)	mm (in.)	570 (22.4)	608 (23.9)	570 (22.4)
LENGTH (N)	mm (in.)	630 (24.8)	610 (24)	691 (27.2)
CAPACITY	STRUCK m ³ (CU.FT.)	0.31 (10.9)		0.36 (12.7)
	HEAPED m ³ (CU.FT.)	0.37 (13.1)		0.45 (16.0)
WEIGHT	kg (lbs.)	150 (331)	180 (397)	136 (300)

DIMENSIONAL SPECIFICATIONS

	LOADER MODEL		LA765
	TRACTOR MODEL		L4701
A	MAX. LIFT HEIGHT (TO BUCKET PIVOT PIN)	mm (in.)	2673 (105.2)
B	MAX. LIFT HEIGHT UNDER LEVEL BUCKET	mm (in.)	2431 (95.7)
C	CLEARANCE WITH BUCKET DUMPED	mm (in.)	2063 (81.2)
D	REACH AT MAX. LIFT HEIGHT (DUMPING REACH)	mm (in.)	537 (21.1)
E	MAX. DUMP ANGLE	deg.	41
F	REACH WITH BUCKET ON GROUND	mm (in.)	1783 (70.2)
G	BUCKET ROLL-BACK ANGLE	deg.	27
H	DIGGING DEPTH	mm (in.)	156 (6.1)
J	OVERALL HEIGHT IN CARRYING POSITION	mm (in.)	1387 (54.6)