

# Kubota Ag Tractors

## M4-061

Competitive Comparison			
FEATURE	Kubota	John Deere	New Holland
Model	M4-061	5065E	Powerstar 65
Engine	V3307	PowerTech 3029	FPT F5D
Type	4-Cylinder Diesel	3-Cylinder	4 Cylinder-Diesel
Rated Engine HP (97/68/EC)	65.4	67	64
PTO HP	52	49	50
Displacement c.u. in.	203	179	207
Rated Engine Speed	2400	2100	2300
Fuel Tank Capacity	23.8	ROPS: 19.0 Cab: 21.0	23.8
Transmisson	Electro Hydraulic-Shuttle, 2 range, F12/R12	Sync Shuttle, 3 Ranges, 9F/3R	Powershuttle, 3 ranges, 12F/12R
Transmission, Opt.	F18/R18 w/creep	12F/12R PowrReverser	NA
Drive Method	4WD	2WD/4WD	4WD
Brakes	Wet disc	Dry/Wet	Wet Disk
PTO Type	Independent	Independent	Independent
Rear PTO	Std. 540 @ 2160	540 @ 2100	540 @ 1948
Hydraulic Flow - Implement GPM	16.7	11.5	12.5
Power Sterring Flow GPM	6.1	6	7.3
Total Flow GPM	22.8	17.5	19.8
Remote Valves: Std/Opt	Deluxe Model: 2 std, 3 opt. Standard Model: 1 std, 2 or 3 opt.	1,2 opt	1 std. opt. 2 & 3
3-Point Hitch Type	Category 1 & 2	Category 2	Category 2
3-Pt Lift Capacity (at link ends) lbs.	4190	3968	4832
3-Pt. Lift @ 24 in. behind link arms lbs.	3307	3192	3664
Wheelbase	84.1	80.7	83.9
Weight	6117	524 4WD Cab: 5919 4WD Rop	6239
Height - ROPS	NA	99.5	NA
Height - Cab	101	95	97.9
Ground Clearance	18.1	2WD: 17.8 4WD: 13.1	15.5
Turning Radius with brakes	11	10.2	np
Turning Radius without brakes	12.2	11.5	12.5
Loader Model	LA1154A	520M NSL & 520 MSL	655TL
Max. Loader Lift Capacity	2928	520M NSL: 3523 520M MSL: 2580	2478
Loader Lift Height	132.7	520M NSL 132	127.2
Std. Bucket Size (inches)	72	73	72
Tire Size Front	9.5-24 R 1	2WD: 7.5-16 F2 4WD: 9.5-24 R1	11.2-24 R1W
Tire Size Rear	16.9-30 R1	16.9-28 R1	16.9 R 30 R1W

\*This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.

# Kubota Ag Tractors

## M4-071

Competitive Comparison			
FEATURE	Kubota	John Deere	New Holland
Model	M4-071	5075E	Powerstar 75
Engine	V3307	Power Tech 3029	F5D
Type	4-Cylinder Diesel	3-Cylinder	4-Cylinder Diesel
Rated Engine HP (97/68/EC)	73.2	75	74
PTO HP	60	57.6	65
Displacement c.u. in.	203	179	207
Rated Engine Speed	2400	2100	2300
Fuel Tank Capacity	23.8	ROPS: 19.0 Cab: 21.0	21.6
Transmission	Electro Hydraulic-Shuttle, 2 Ranges, F12/R12	Sync Shuttle, 3 Ranges, 9F/3R	Powershuttle, 3 Range, 12F/12R
Transmission, Opt.	F18/R18 w/creep	12F/12R PowrReverser	F12/R12 Mechanical, F20/R20 Powershuttle w/creep
Drive Method	4WD	2WD/4WD	4WD
Brakes	Wet disc	Dry/Wet	Wet Disc
PTO Type	Independent	Independent	Independent
Rear PTO	Std. 540 @ 2160	540 @2100	540 @ 2300
Hydraulic Flow - Implement GPM	16.7	11.5	12.5
Power Steering Flow GPM	6.1	6	7.3
Total Flow GPM	22.8	17.5	19.8
Remote Valves: Std/Opt	2 std, 3 opt. Standard Model: 1 std, 2 opt.	1,2 opt	2 opt. 3
3-Point Hitch Type	Category 1 & 2	Category 1 & 2	Category 2
3-Pt Lift Capacity (at link ends) lbs.	4190	3968	n/p
3-Pt. Lift @ 24 in. behind link arms lbs.	3307	3192	3664
Wheelbase	84.1	80.7	83.9
Weight	6117	2WD: 4524 4WD Cab: 5919 4WD Rops: 6702	2WD Rops 5027 Cab: 5622 4WD Rops: 5952 Cab: 6239
Height - ROPS	NA	99.5	NA
Height - Cab	101	95	100.2
Ground Clearance	18.1	2WD: 17.8 4WD: 13.1	16.7
Turning Radius with brakes	11	10.2	np
Turning Radius without brakes	12.2	11.5	12.5
Loader Model	LA1154A	520M NSL & 520 MSL	655TL
Max. Loader Lift Capacity	2928	520M NSL: 3523 520M MSL: 2580	2478
Loader Lift Height	132.7	520M NSL 132	127.2
Std. Bucket Size (inches)	72	73	72
Tire Size Front	9.5-24 R 1	7.5-16 F2 4WD: 9.5-24 R 1	11.2-R24
Tire Size Rear	16.9-30 R1	16.9-28 R1	16.9-R30

\*This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.